



HIGHNESS™

27" SURGICAL DISPLAY

- ◆ FHD LED
- ◆ Premium Choice of Surgeons for Laparoscopic Procedures
- ◆ CE, ISO, RoHS Complaint



Applications:

- Laparoscopy
- GI Endoscopy
- Bronchoscopy
- Surgical Microscopy
- Arthroscopy
- Neuro-Spine Surgery
- Digital OR

MHSD-2720



TECHNICAL SPECIFICATIONS

Model	MHSD-2720
Screen Technology	TFT AM LCD
Active Screen Size (Diagonal)	27"
Active Screen Size (H x V)	597.888 x 336.312 mm
Aspect Ratio	16:9
Resolution	1920 x 1080
Pixel Pitch	0.3114 mm
Viewing Angle (H, V)	178°, 178°
Maximum Luminance	900 cd/m ²
Contrast Ratio	1000:1
Color	1.07 Billion
Response Time (Tr + Tf)	14 ms
Video Inputs Signals	Digital :- 3G-SDI & DVI Analog :- VGA, CVBS & S-Video Digital Input :- BNC & DVI
Interface Port	Analog Video :- 15 Pin D-Sub, RCA & Mini Din Digital Output :- BNC
Video Outputs Signals	Digital :- 3G-SDI
Power Requirements (Nominal)	110~240V AC
Power Consumption (Nominal)	90W Max
Power Saving	EPA, VESA Standard
Operating Temperature	0 to +50°C
Storage Temperature	-20 to +60°C
Relative Humidity	10% to 90% (Non Condensing)
Housing Color	White
Housing Material	Metal
Mounting Standard	VESA (100 mm)
Supplied Accessories	Cable (VGA, DVI, S-Video, BNC & Power Cord), Manual
Warranty	2 Years
Applications	Laparoscopy, GI Endoscopy, Bronchoscopy, Surgical Microscopy, Arthroscopy, Neuro-Spine Surgery, Digital OR



HIGHNESS MICROELECTRONICS PVT. LTD.

📍 101-103, Elecon Chambers, Sakinaka MTNL Road, Andheri (E), Mumbai - 400 072. India.

☎ +91 22 6863 6500 | 📞 +91 22 4026 4263

🌐 www.highnessmicro.com

✉ sales@highnessmicro.com



VOL M-L 1.0, June 2019

An ISO 9001:2015 Company. Copyright @ 2019 Highness Microelectronics Pvt. Ltd. All Rights Reserved.

All images are for representation purpose only. All images and content are copyrighted & copy, reprint or reproduction without written permission prohibited.